

# DRY TENDER TRAILER

BUILT TO HAUL | BUILT TO LAST

## Standard Equipment

<b>Frame Length</b>	25' or 34' Lower Deck; 11' Upper Deck
<b>Frame Width</b>	39'
<b>Frame</b>	I-Beam; I-Beam Fifth Wheel
<b>Capacity</b>	45,000 GVWR
<b>Axle</b>	(1) 22,500 lb. Oil Bath Heavy Duty Axle with Anti Lock Air Brakes with Automatic Slack Adjusters and Park Brake
<b>Axle</b>	(1) 22,500 lb. Oil Bath Heavy Duty Axle with Air Brakes with Automatic Slack Adjusters and Park Brake
<b>Suspension</b>	Hutch Suspension 9700 3-point
<b>Wheels</b>	(8) 22.5" x 8.25" Budd Style Dual Wheel with 10 on 11.25"
<b>Tires</b>	(8) 255/70R-22.5 Tire, New
<b>Jack</b>	Holland Landing Gear Set 2-Speed Jack, Handle and Crosspipe
<b>Hitch</b>	King Pin, 48" Ground Clearance, 2" SAE with 3/8" Bolster Plate
<b>Lighting</b>	DOT Approved, All Sealed Rubber Mounted
<b>Finish</b>	Powder Coat--Black; Prepped, Bead Blasted and Acid Washed
<b>Other</b>	Mud Flaps Reflector Tape

Ask dealer about available options.

*Behnke Enterprises, Inc. reserves the right to make changes without notification.*



BEHNKE ENTERPRISES, INC.

800 NINTH AVE. | FARLEY, IOWA 52046  
PH. 563-744-3246 | FAX 563-744-9066  
[www.behnkeenterprises.com](http://www.behnkeenterprises.com)