

14,000 GVW • 16,000 GVW • 18,000 GVW • 20,000 GVW

Sprayer Trailer *Pull-Type*

24,000 GVW • 30,000 GVW • 40,000 GVW • 45,000 GVW



16" Adjustable side ramps as on 14,000 GVW & 16,000 GVW



Optional gooseneck and wood deck available



16" Flip-up style outriggers as on 18,000 GVW+



Manufactured by:

BEHNKE ENTERPRISES, INC.
800 Ninth Ave. NW | Farley, Iowa 52046
Ph. 563-744-3246 | Fax 563-744-9066
www.behnkeenterprises.com



Sprayer Trailer

14,000 lb. GVW

Main Frame	8" Channel
Capacity	14,000 lb. GVW
Frame Width	48" or 59"
Axle	(2) 7,000 lb. Dexter EZ Lube
Brakes	Both Axles, Electric or Surge
Hitch	Adjustable 2 5/16" Ball, Pin or Pintle Hitch
Jack	Heavy Duty 10,000 lb., Sidewind
Tire	ST235-80R-16E Radial Tires
Wheel	White Spoke
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting 16" Adjustable Side Ramps • Reflector Tape Safety Chains • Breakaway Safety Kit Tool Box • Wheel Stops Flip-up Load Ramps • D-Ring Tie Downs

Optional Features

Heavy Duty Fenders (single wheel) • Gooseneck 2 5/16 Coupler • Spare Tire and Wheel • Steel, Wood or Mesh Decking Available

18,000 lb. GVW

Main Frame	12" I Beam, 14 lbs.
Capacity	18,000 lb. GVW
Frame Width	45" dual or 59" single
Axle	(2) 9,000 lb. Dexter Oil Bath
Brakes	Both Axles, Electric
Hitch	Adjustable 2 5/16" Ball, Pin or Pintle Hitch
Jack	Heavy Duty 10,000 lb., Sidewind
Tire (Single)	215-75R-17.5 Tire
Tire (Dual)	ST235-80R-16D Tire
Wheel	OEM Wheels
Outriggers	16" Flip-up Style
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting 16" Adjustable Side Ramps • Reflector Tape Safety Chains • Breakaway Safety Kit Tool Box • Wheel Stops Flip-up Load Ramps • D-Ring Tie Downs

Optional Features

Heavy Duty Fenders (dual wheel) • Gooseneck 2 5/16 Coupler • 20" Outrigger Trays • Spare Tire and Wheel • Steel, Wood or Mesh Decking Available In Frame Width or Full Width

24,000 lb. GVW

Main Frame	12" I Beam, 22 lbs.
Capacity	24,000 lb. GVW
Frame Width	41"
Axle	(2) 12,000 lb. Dexter Oil Bath
Brakes	Electric or Air, Both Axles
Hitch	Adjustable Pintle Hitch
Jack	Heavy Duty 10,000 lb., Sidewind
Tire (Dual)	ST235-80R-16"E
Wheel	OEM Wheels
Outriggers	16" Flip-up Style
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting Reflector • Tape Safety Chains Breakaway Safety Kit • Tool Box Wheel Stops • Flip-up Load Ramps • D-Ring Tie Downs

Optional Features

Heavy Duty Fenders (dual wheel) • Gooseneck 2 5/16 Coupler • Spare Tire and Wheel • 20" Outrigger Trays • Steel, Wood or Mesh Decking Available In Frame Width or Full Width

40,000 lb. GVW

Main Frame	16" I Beam, 26 lbs.
Capacity	40,000 lb. GVW
Frame Width	39"
Axle	(1) 20,000 lb. Dexter oil bath axle with anti lock air brakes automatic slack adjusters and park brake
Axle	(1) 20,000 lb. Dexter oil bath axle with air brakes automatic slack adjusters and park brake
Brakes	Air
Hitch	Adjustable Pintle Hitch
Jack	12,000 lb. Dropleg Jack, Sidewind
Tire (Dual)	235-75R-17.5
Wheel	17.5 x 6.75 OEM Wheels
Outriggers	16" Flip-up Style
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting Reflector Tape • Safety Chains Tool Box • Wheel Stops Flip-up Load Ramps • D-Ring Tie Downs

Optional Features

Heavy Duty Fenders (dual wheel) • 20" Outrigger Trays • Spare Tire and Wheel • Steel, Wood or Mesh Decking available in frame width or full width

16,000 lb. GVW

Main Frame	8" Channel
Capacity	16,000 lb. GVW
Frame Width	48" or 59"
Axle	(2) 8,000 lb. Dexter Oil Bath
Brakes	Both Axles, Electric or Surge
Hitch	Adjustable 2 5/16" Ball, Pin or Pintle Hitch
Jack	Heavy Duty 10,000 lb., Sidewind
Tire	215-75R-17.5 Tire and Wheel
Wheel	OEM Wheels
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting 16" Adjustable Side Ramps • Reflector Tape Safety Chains • Breakaway Safety Kit Tool Box • Wheel Stops Flip-up Load Ramps • D-Ring Tie Downs

20,000 lb. GVW

Main Frame	14" I Beam, 19 lbs.
Capacity	20,000 lb. GVW
Frame Width	45" dual or 59" single
Axle	(2) 10,000 lb. Dexter Oil Bath
Brakes	Electric or Air, Both Axles
Hitch	Adjustable 2 5/16" Ball, Pin or Pintle Hitch
Jack	Heavy Duty 10,000 lb.
Tire (Single)	215-17.5" Radial
Tire (Dual)	ST235-80R-16D Tire
Wheel	OEM Wheels
Outriggers	16" Flip-up Style or 16" Slide-In
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting 16" Adjustable Side Ramps • Reflector Tape Safety Chains • Breakaway Safety Kit Tool Box • Wheel Stops Flip-up Load Ramps • D-Ring Tie Downs

30,000 lb. GVW

Main Frame	14" I Beam, 26 lbs.
Capacity	30,000 lb. GVW
Frame Width	41"
Axle	(2) 15,000 lb. Dexter Oil Bath
Brakes	Electric or Air, Both Axles
Hitch	Adjustable Pintle Hitch
Jack	12,000 lb. Dropleg Jack, Sidewind
Tire (Dual)	215-75R-17.5
Wheel	OEM Wheels
Outriggers	16" Flip-up Style
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting Reflector • Tape Safety Chains Breakaway Safety Kit • Tool Box Wheel Stops • Flip-up Load Ramps • D-Ring Tie Downs

45,000 lb. GVW

Main Frame	16" I Beam, 26 lbs.
Capacity	45,000 lb. GVW
Frame Width	39"
Axle	(1) 22,500 lb. Dexter oil bath axle with anti lock air brakes, automatic slack adjusters and park brake
Axle	(1) 22,500 lb. Dexter oil bath axle with air brakes, automatic slack adjusters and park brake
Brakes	Air
Hitch	Adjustable Pintle Hitch
Jack	12,000 lb. Dropleg Jack, Sidewind
Tire (Dual)	255/70R-22.5" Radial
Wheel	22.5 x 8.25" Budd Style Dual Wheel w/ 10 on 11.25"
Outriggers	16" Flip-up Style
Finish	Powder Coat-Black
Other	DOT Approved Sealed Lighting Reflector Tape • Safety Chains Tool Box • Wheel Stops Flip-up Load Ramps • D-Ring Tie Downs