## DETACH

Hydraulic Non Ground Bearing

70,000 GVW



Manufactured by:

Behnke Enterprises, Inc. ■ 800 9th Ave. NW, Farley, IA 52046 ■ Ph. (563)744-3246 ■ Fax (563)744-9066



## **Hydraulic Non Ground Bearing**

## 70,000 GVW

## DETACH





Standard Equipment	BHDG70	BHDG102	BHDG110
Capacity (in 12')	Χ	X	X
10' 7" Gooseneck (14" KP setting with 86" Swing Clearance)	Χ	X	NA
13' Gooseneck (16" KP setting with 113" Swing Clearance)	NA	NA	X
50" Loaded 5th Wheel Height	X	X	X
2nd King Pin Setting (40" KP Setting with 89" Swing Clearance)	NA	NA	X
Gooseneck does not require ground bearing pads	Χ	X	Χ
Hydraulic self-lifting neck	X	X	X
Hydraulic self alignment cylinder	X	X	X
102" Overall Deck Width	X	X	X
22" Front Loading Ramps (With Tracktion Bars)	Χ	X	X
24" Loaded Deck Height	X	X	X
Deck Length	24'	25' 11"	25' 11"
4-Beam Main Frame Construction	X	X	X
10" I-Beam on 24" Centers	Χ	X	X
1 3/4" Oak Decking Raised	X	X	X
(16) D-rings On Deck, (4) D-rings on Wheel Area	Χ	X	X
Chain Slot Tie Downs Every 24" On Main Deck	Χ	X	X
Knuckle Trough At Rear of Deck (1/4" Steel Plate)	X	X	X
Mesh Between Beams For Chain Storage At Rear of Deck	Χ	X	X
Boom Trough in Wheel Area	X	X	X
25,000 lb. Axles	Tandem	Triple	Triple
3rd Axle Air Lift	NA	X	X
Air Ride Suspension	Χ	X	X
Frame Reinforced For Flip Axle	Χ	X	X
LED Lights (With Strobe Lights)	Χ	X	X
Rubber Mounted Sealed Lights and Sealed Harness	Χ	X	X
Air, Electrical and Hydraulics Installed After Paint	Χ	X	X
Media Blasted and Acid Washed Prior to Powder Coat	Χ	X	X
Zinc Rich Primer and Powder Coat Finish (Black)	Χ	X	X
Flag Holders and Wide Load Sign Brackets	Χ	Χ	X
Mud Flap Brackets	Χ	Χ	Χ
Quick Couplers 3000 PSI/17 GPM	X	X	X